



# Zalakerámia

## Data sheet

|                  |                                   |                |             |
|------------------|-----------------------------------|----------------|-------------|
| Type of product: | glazed                            | ceramic tile   | dry pressed |
| Norm:            | EN 14411 Annex L E>10% BIII group |                |             |
| Glaze:           | glazed                            |                |             |
| Surface:         | glossy                            |                |             |
| Product line:    | Carneval                          | negru lucios   |             |
| Catalogue code:  | <b>ZBK 62009</b>                  | 2064-0131-3521 |             |
| Normal size:     | 20x60x0,9 cm                      |                |             |
|                  | 201x601 mm                        | Kaliber 1      |             |
|                  | 200x600 mm                        | Kaliber 0      |             |
|                  | 199x599 mm                        | Kaliber 9      |             |
|                  | 199x598 mm                        | Kaliber 8      |             |

| <i>essential characteristics</i>                | <i>inspection method</i> | <i>nominal value</i> | <i>Zalakerámia production</i> |
|---|--------------------------|----------------------|-------------------------------|
| length and width                                | ISO 10545-2              | $\pm 0,5\%$          | $\pm 0,3\%$                   |
| thickness                                       | ISO 10545-2              | $\pm 10\%$           | $\pm 3,0\%$                   |
| rectangularity                                  | ISO 10545-2              | $\pm 0,5\%$          | $\pm 0,3\%$                   |
| straightness of edges                           | ISO 10545-2              | $\pm 0,3\%$          | $\pm 0,25\%$                  |
| curvature of edges                              | ISO 10545-2              | $\pm 0,5\%$          | + 0,3%                        |
| centre curvature                                | ISO 10545-2              | $\pm 0,5\%$          | + 0,3%                        |
| water absorption                                | ISO 10545-3              | E >10%               | average 18%                   |
| bending strength N/mm <sup>2</sup>              | ISO 10545-4              | min. 12-15           | average 20                    |
| thermal shock resistance                        | ISO 10545-9              | required             | as per norm                   |
| chemical resistance against household chemicals | ISO 10545-13             | min. GB              | as per norm                   |
| resistance against pool chemicals               | ISO 10545-13             | min. GB              | as per norm                   |
| wear resistance                                 | ISO 10545-7              | not required         | -                             |
| frost resistance                                | ISO 10545-12             | not required         | -                             |

Hereby we confirm, that above mentioned product complies with rules of EN 14411 norm.

Tófej, 06.08. 2021.

ZALAKERÁMIA Zártkörűen Működő  
Részvénytársaság  
8946 Tófej Rákóczi út 44.  
ZALAKERÁMIA ZR