



# Zalakerámia

## Data sheet

Type of product:	glazed	ceramic tile	dry pressed
Norm:	EN 14411 Annex L E>10% BIII group		
Glaze:	glazed		
Surface:	matt		
Product line:	GEO		
Catalogue code:	<b>ZBD 62160</b>	2064-0242-3521	
	<b>ZBD 62164</b>	2064-0243-3521	
Normal size:	20x60x0,9 cm		
	201x601 mm	Kaliber 1	
	200x600 mm	Kaliber 0	
	199x599 mm	Kaliber 9	
	199x598 mm	Kaliber 8	

<i>essential characteristics</i>	<i>inspection method</i>	<i>nominal value</i>	<i>Zalakerámia production</i>
length and width	ISO 10545-2	± 0,5%	± 0,3%
thickness	ISO 10545-2	± 10%	± 3,0%
rectangularity	ISO 10545-2	± 0,5%	± 0,3%
straightness of edges	ISO 10545-2	± 0,3%	± 0,25%
curvature of edges	ISO 10545-2	± 0,5%	+ 0,3%
centre curvature	ISO 10545-2	± 0,5%	+ 0,3%
water absorption	ISO 10545-3	E >10%	avarage 18%
bending strength N/mm2	ISO 10545-4	min. 12-15	avarage 20
thermal shock resistance	ISO 10545-9	required	as per norm
chemical resistance against household chemicals	ISO 10545-13	min. GB	as per norm
resistance against pool chemicals	ISO 10545-13	min. GB	as per norm
wear resistance	ISO 10545-7	not required	-
frost resistance	ISO 10545-12	not required	-

Hereby we confirm, that above mentioned product complies with rules of EN 14411 norm.

Tófej, 29. 08. 2022.

ZALAKERÁMIA Zártkörűen Működő  
Részvénytársaság  
8946 Tófej, Rákóczi út 44.  
ZALAKERÁMIA ZRT.