



Zalakerámia

Data sheet

Type of product:	glazed	ceramic tile	dry pressed
Norm:	EN 14411 Annex L E>10% BIII group		
Glaze:	glazed		
Surface:	matt		
Product line:	GEO		
Catalogue code:	ZBD 62161	2064-0244-3501	
	ZBD 62162	2064-0245-3501	
Normal size:	20x60x1 cm		
	201x601 mm	Kaliber 1	
	200x600 mm	Kaliber 0	
	199x599 mm	Kaliber 9	
	199x598 mm	Kaliber 8	

<i>essential characteristics</i>	<i>inspection method</i>	<i>nominal value</i>	<i>Zalakerámia production</i>
length and width	ISO 10545-2	± 0,5%	± 0,3%
thickness	ISO 10545-2	± 10%	± 3,0%
rectangularity	ISO 10545-2	± 0,5%	± 0,3%
straightness of edges	ISO 10545-2	± 0,3%	± 0,25%
curvature of edges	ISO 10545-2	± 0,5%	+ 0,3%
centre curvature	ISO 10545-2	± 0,5%	+ 0,3%
water absorption	ISO 10545-3	E >10%	average 18%
bending strength N/mm ²	ISO 10545-4	min. 12-15	average 20
thermal shock resistance	ISO 10545-9	required	as per norm
chemical resistance against household chemicals	ISO 10545-13	min. GB	as per norm
resistance against pool chemicals	ISO 10545-13	min. GB	as per norm
wear resistance	ISO 10545-7	not required	-
frost resistance	ISO 10545-12	not required	-

Hereby we confirm, that above mentioned product complies with rules of EN 14411 norm.

Tófej, 29. 08. 2022.

ZALAKERÁMIA Zártkörűen Működő
Részvénytársaság
8946 Tófej, Rákóczi út 44.
ZALAKERÁMIA ZRT.

ZALAKERÁMIA ZÁRTKÖRŪEN MŰKÖDŐ RÉSZVÉNYTÁRSASÁG
8946 Tófej Rákóczi út 44. Pf.: 1. Telefon: (92) 566 400, Fax: (92) 369 070
Budapesti Iroda: 1239 Budapest, Grassalkovich út 255. Tel.: (1) 289 5101, Fax: (1) 286 0183