

Technical data sheet

Product: WLAVD506	Nominal size: 60x5 cm
Color: brown	Work size: 598x48x10 mm
Type of product: wall tile - listel	Editing edges: rectified
Surface: flat matt	Norm: EN 14 411:2016,annex L BIII
Series: Next	

Technical characteristics	Norm	EN 14 411:2016 annex L BIII	LB/RAKO
Dimensions and surface quality			
- Length / width	ISO 10545-2	± 0,5%	± 0,4%
- Thickness	ISO 10545-2	± 10%	± 5%
- Straightness	ISO 10545-2	± 0,3%	± 0,2%
- Rectangularity	ISO 10545-2	± 0,5%	± 0,3%
- Surface flatness	ISO 10545-2	± 0,5%	± 0,25%
- Surface quality	ISO 10545-2	Min. 95%	Min. 95%
Water absorption	ISO 10545-3	E>10%	E>10%
Modulus of rupture	ISO 10545-4	Min. 12 N/mm2 Ind.min. 15 N/mm2	Min. 12 N/mm2 Ind.min. 15 N/mm2
Breaking strength	ISO 10545-4	# 7,5 mm min. 600 N # 7,5 mm min. 200 N	# 7,5 mm min. 600 N # 7,5 mm min. 200 N
Coefficient of linear thermal expansion	ISO 10545-8	Declared value	Max. 0,000008 / K
Crazing resistance	ISO 10545-11	Required	Resistant
Thermal shock resistance	ISO 10545-9	Required	Resistant
Resistance to acid and alkali			
- low concentrations	ISO 10545-13	Declared value	GLB
- high concentrations	ISO 10545-13	Declared value	GHB
Resistance to house and pools chemicals	ISO 10545-13	Min. GB	GA
Resistance to staining	ISO 10545-14	Min. 3	Min. 3
Lead release	ISO 10545-15	Declared value	Pb max. 0,80 mg/dm2
Cadmium release	ISO 10545-15	Declared value	Cd max. 0,07 mg/dm2
Surface hardness according to Mohs	EN 101	Not required	Min. 3